

# DE 35 EC (VN)

## INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 205237

Enjoy hot water on demand at any time

A compact instantaneous water heater supplies domestic hot water on demand. With a non-slip power selector, the DE shower water heater provides you with convenient, stepless temperature adjustment at an affordable price. The minimalist white design blends perfectly into any bathroom decor.



The pleasure of water without the worries

The built-in Earth Leakage Circuit Breaker (ELCB) detects any harmful leakage current and shuts off the power supply, thereby providing full protection from electric shock for you and your family. Moreover, our water heater is built according to the latest technical standard including EMC compatibility, for worry-free operation.

### The main features

Temperature adjustment via stepless power control

Complete set optimised for a single shower

Highly efficient composite polymer tank for reduced heat loss and electricity consumption

Corrosion-free copper heating element for longer service life

5-in-1 shower head with wall mounting bracket

Compact design for space saving installation

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

Protection class IP25 (splash-proof)

Temperature adjustment via stepless power control

Complete set optimised for a single shower

Certified electromagnetic compatibility

---

Highly efficient composite polymer tank for reduced heat loss and electricity consumption

---

Corrosion-free copper heating element for longer service life

---

5-in-1 shower head with wall mounting bracket

---

Compact design for space saving installation

---

Anti-scalding and overheating protection with double action thermostat

---

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

---

Quick and easy installation

---

Protection class IP25 (splash-proof)



Type	DE 35 EC (VN)	DE 45 EC (VN)
Part no.	205237	205238

## Technical data

Cold water connection	1/2 inch	1/2 inch
Electrical fuse protection	ELCB	ELCB
Rated output	3,500 W	4,500 W
Electrical connection	1/N/PE~220-240 V	1/N/PE~220-240 V
Rated voltage	220-240 V	220-240 V
Rated current	15.9 A	20.45 A
Display	without	without
Heating element	Copper tubular	Copper tubular
Type	Open outlet	Open outlet
Automatic flow switch	true	true
Heating material	Plastic	Plastic
Temperature setting	Variable	Variable
Temperature control	Output control	Output control
Anti-scalding protection	Double acting thermostat	Double acting thermostat
Shower accessories	5-in-1 shower head with wall mounting bracket	5-in-1 head shower with slide bar
Colour	white	white
IP rating	IP25	IP25
Shutdown value	0.8 l/min	0.8 l/min
Starting flow rate	1.3 l/min	1.3 l/min
Depth	78 mm	78 mm
Height	308 mm	308 mm
Width	184 mm	184 mm

Weight

1 kg

1 kg

#### Contact information

You have questions? We appreciate to help you:

Call 1800 888822

Write an email to [info@stiebel-eltron.vn](mailto:info@stiebel-eltron.vn)

#### Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in.

The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.