

# ESH 30 B Trend (VN)

WALL MOUNTED CYLINDER

PRODUCT-NO.: 207016

## The main features

Supplies several draw-off points with hot water

Precise temperature control with capillary thermostat

User friendly temperature selection up to 75 °C with rotary selector

Maintenance-free, enamelled heating element

Durable and corrosion-resistant casing

Highest safety standards due to integrated RCD (ELCB)





<b>Type</b>	ESH 15 B Trend (VN)	ESH 30 B Trend (VN)
<b>Part no.</b>	207015	207016

## Technical data

<b>Height</b>	380 mm	440 mm
<b>Width</b>	311 mm	370 mm
<b>Installation type</b>	Wall mounted, vertical	Wall mounted, vertical
<b>Protective anode</b>	Sacrificial magnesium anode	Sacrificial magnesium anode
<b>Safety valve</b>	Pressure safety valve	Pressure safety valve
<b>IP rating</b>	IP25	IP25
<b>Type of control</b>	Thermostatic	Thermostatic
<b>Cable length</b>	1.5 m	1.5 m
<b>Cylinder material</b>	steel, enamel	steel, enamel
<b>Heating element material</b>	Incoloy + enamel	Incoloy + enamel
<b>Thermal insulation material</b>	PU foam	PU foam
<b>Temperature range</b>	up to 75 °C	up to 75 °C
<b>Nominal capacity</b>	15 l	30 l
<b>Max. water inlet pressure</b>	0.75 MPa	0.75 MPa
<b>Electrical connection</b>	1/N/PE~220-240 V	1/N/PE~220-240 V
<b>Rated voltage</b>	220-240 V	220-240 V V
<b>Rated current</b>	11 A	11 A
<b>Rated output</b>	2,500 W	2,500 W

#### Contact information

You have questions? We appreciate to help you:

Call 1800 888822

Write an email to [info@stiebel-eltron.vn](mailto:info@stiebel-eltron.vn)

#### Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in.

The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.